

## ADHESIVES

### CONTACT CEMENT

Stock No.: **CONTACTR5** red -5gal  
**CONTACTN5** neutral-5gal  
**CONTACTN1** natural-1gal

Type - Flammable  
 Spray/Roller

Manufacturer - Slocum Adhesives

Solvents - Petroleum Based

Coverage - 200 s.f./gal (spray-  
 single surface)  
 360 s.f./gal. (rolled-  
 both surfaces)

Thinner/Cleaner - **LACTHIN5**

Solids - 18%



### ADHESIVES & GLUES

Stock No.      Size  
**YELLOW8**      8 oz  
**YELLOW1**      gallons  
**YELLOW5**      5 gallon bucket  
 Professional quality, 44% solids, al-  
 ic resin wood glue. Sets fast. Water  
 sistant.



phat-  
 re-



**ROO CLEAR** is a ready-to-use acrylic emulsion adhesive capable of bonding a variety of materials and substrates. It is especially well suited for bonding difficult substrates like melamine and vinyl surfaces to porous substrates such as wood and wood composite materials. RooClear dries quickly to produce a clear, water resistant and elastomeric bond with very high tensile strength.

All application surfaces must be clean and dry. RooClear should be used as instructed. For general assembly, first apply adhesive to porous surface, then join the two surfaces together. Assemble while the adhesive is still wet. Clamping, staples, and/or screws are suggested to create a snug fit. Clean up excess wet glue with water. When glue is dry use denatured alcohol.

RooClear will bond to many materials including: melamine, vinyl, high pressure laminates (Formica, Wilsonart), PVC edgebanding, metal, stone, tile, acrylics wood veneer, paper and fabric, crafts, rubber and even painted and UV coated surfaces. Stocked in gallons **ROOCLEAR1**, See website for complete details.



**2P-10 ADHESIVE SYSTEM** can easily glue the hardest joints in cabinetry without clamping. Jel – will not run, all-purpose application, excellent for vertical surfaces. Thick – for use on porous surfaces such as particle board. Medium – for use on smooth surfaces such as melamine & laminate; excellent crack wicking properties. Thin – excellent micro crack filling & precision mending; zero glue line.

<b>2P10ACTIVATOR</b>	12 OZ	Activator
<b>2P10DEBONDER</b>	2OZ	Debonder refill
<b>2P10MICROTIP</b>	25/PK	Micro-Tips
<b>2P10PINCAPS</b>	5/PK	Pin Caps
<b>2P10JEL</b>	8 OZ	Jel
<b>2P10MED</b>	8 OZ	Medium
<b>2P10THICK</b>	8 OZ	Thick



**PLASTIC RESIN GLUE** (or Urea-Formaldehyde Glue) is powdered, pre-catalyzed water-activated glue that provides strong, durable bonds for wood and wood products, including veneers and laminates to substrate, chopping blocks, jointing plates, etc. See website for complete details.

<b>PLASTICRES45</b>	4-1/2 lb container
<b>PLASTICRES25</b>	25 lb container



**RESORCINOL GLUE** is a two-part adhesive that provides the strongest, most durable bond for severe service application. Once cured, it withstands continuous salt or fresh water immer-

sion, tropical to sub-zero temperatures, solvents, mild acids and alkalis, resists fungi, bacteria, insects, and molds. Suitable to laminate structural wood beams, wood, particleboard, and cured concrete. See website for complete details

**RESORCINOL**      quarts

**AEROSOL ADHESIVES**


Common Uses - High pressure laminates  
 Bond Features - High strength contact  
 Properties - Non-Misting  
 Spray Pattern - Web  
 Initial Shear Strength - 50  
 Ultimate Shear Strength - 230  
 Two Surface Bond - 30 sec-30 min  
 1 - 15 Min.  
 Can Size - 16 oz.  
 Stock Number - **CONTACTAEROSOL**



Hotmelt glue sticks are suitable for wood, ceramics, leather, canvas, metal, and plastic. Hold surfaces together for 15 seconds, glue sets in 30 - 60 seconds. AP-10 (all purpose, 10" sticks x .045), sold by the dozen or full boxes. **GLUESTICK10**



**HOT MELT**



<u>Product Name</u>	<u>Physical Configuration</u>	<u>Color</u>
<b>HMNATHPL</b>	pellets (55# bag)	natural
<b>HMBRNHPL</b>	pellets (55# bag)	ivory
<b>HMNATCART</b>	cartridges (45/bx, 35 #)	brown
<b>HMWHICART</b>	cartridges (45/bx, 35 #)	natural
		white